



sunwaterlife™
L'EAU POTABLE POUR TOUS



GENERAL CHARACTERISTICS

- ✔ Use two ultrafiltration membranes, certified NSF - ANSI, which filter bacteria and viruses.
- ✔ Complying with the OMS specification for drinkable water.
- ✔ Integrated in a solid suitcase (NATO specifications).



Deployed in less than 5 minutes



Manual backwashing of the membranes



Up to 300 liters per hour

AQUALINK UF

Aqualink UF's Technical Features

Flow rate	Up to 300 liters / hour
Daily use	8 to 10 hours
Solar panel	130 Wc
Weight	23 kg
Size	550 x 450 x 270 mm
Geometric suction height	2 meters
Discharge head	7 meters

Terms of service

Water temperature	2 à 35°C
pH	2 à 12
Chlorine	0 to 5 mg/L
TH	Indifferent

APPLICATIONS



Health

Provide healthcare facilities and medical centres with pure water.



Civil & Military Security

Provide a drinking water network in emergency situations : floods, earthquakes, typhoons, landslides...



Housing

Provide houses and apartments with drinking water.

Sunwaterlife SAS 1, Place Pierre Potier - 31100 Toulouse

+33 9 54 36 72 49 / +33 7 60 77 57 24 - contact@sunwaterlife.com - www.sunwaterlife.com